



PRODUCT TECHNICAL DATA SHEET

Issue:
2007 Dec 19th

29mm Crown Glass Bottle Finish PE Plastic Plug “OBTURATEUR DAP”

General Information

The closure device “Obturateur DAP” is a PE plastic plug suitable for application on 29mm champenoise glass bottle finishes with internal volume of 1/2, 1 and 2 liters, compliant to AFNOR NF H 35-022 et NF H35-029 standards, with function of :

- contribution to liquid and gas tightness, in combination with crown cork, after capping and during the disgorging (“dégorgement”)
- collect wine yeast sediments and protect the internal side of the 10mm final section of the bottle neck from impurities deposits.
- orientate and make comfortable the yeast sediments ejection.



Technical features :

Description:	Plastic plug suitable for application on 29 mm champenoise bottle finishes in compliance with AFNOR NF-H35-022 et NF-H35-029 standards
Diameter of the plug body:	18.15 ± 0.10 mm
Diameter of the plug ring:	19.05 ± 0.15 mm
Diameter of the entry plug cone:	16.20 ± 0.20 mm (base of cone section)
Total height:	14.50 ± 0.20 mm
Material:	LDPE (LowDensityPolyEthylene) free of any additive and made only by virgin plastic materials (no recycled plastics).
Average weight:	1.02g

Lab performances and others :

Food compliance:	Compliant for direct contact with food - Refer to relevant food compliance statement
Environment:	94/62CE compliant - Refer to relevant environmental compliance statement
Condition d'utilisation:	For optimal results on application refer to guideline <i>GUIDE DE L'EMBOUEILLAGE N°3- BOUCHAGE DE TIRAGE ET D'EXPEDITION / doc INE 93/006</i>
Application / performances:	The application, and the related performance of the closure, has to be verified at every change in the used materials parameters, with special reference to the design of the bottle finish, and the specific closing equipment used. Please consult your Pelliconi representative if in doubt.
Storage:	The plugs (“Obturateurs”) should be stored in a clean, well ventilated, dry place, avoiding direct sunlight, high temperatures, and exposure to volatile contaminants, and must not be stacked.
Standard Packaging:	Carton Box with 6.500 plugs, 7 boxes for layer, 6 layers per pallet. For a total amount of 273.000 plugs per pallet. Carton: dimensions (intérieurs), 462x307x269 mm Palette (lot): dimensions 1200x1000x1890 mm pour 42 cartons Other packaging solutions available on demand.

This document is the property of PELLICONI GROUP and cannot be reproduced, used or issued to third parties without specific written authorization of PELLICONI GROUP that retains the right to take legal action. This document replaces all previous releases and is intended for commercial purposes only, therefore it can be modified at anytime due to technical, and/or commercial reason, without any prior notification and revisions are not automatically issued. The process parameters are not suggested because they are depending on different typologies of fixtures and fittings. The food contact suitability for aggressive foods and/or production cycles (ex. High temperature pasteurisation) has to be verified with tests by the end-user. This document has been written on the basis of our knowledges at issue date, the informations reported refer exclusively to the product in hand, and they are not guarantee of unexpressed qualities.

